

IARU Region 1 HF-taajuusjakosuositus 16.10.2020 alkaen
Tehot ja taajuusalueet määräyksen TRAFICOM/185774/03.04.05.00/2021 mukaan

Taajuus (kHz)	Suosittelut lähetystapa ja käyttötarkoitus	Tehoraja Yleisluokka	Tehoraja Perusluokka	Suurin suositeltu kaistanleveys	Status
136 kHz/2200 m 135,7-137,8 kHz (2,1 kHz)					
135,7-137,8	CW, QRSS and narrow band digital modes	1 W (EIRP)	1 W (EIRP)	200 Hz	Sec
472 kHz/630 m 472-479 kHz (7 kHz)					
472-475	CW	1 W (EIRP)	1 W (EIRP)	200 Hz	Sec
475-479	CW, digimodes	1 W (EIRP)	1 W (EIRP)	500 Hz	Sec
1,8 MHz/160 m 1810-1850 kHz (40 kHz), 1850-2000 kHz (150 kHz)					
1810-1838	CW	1500 W	120 W	200 Hz	Pri
1838-1840	1836 QRP Centre of Activity				
1838-1840	Narrow band modes	1500 W	120 W	500 Hz	Pri
1840-1843	All modes - digimodes	1500 W	120 W	2700 Hz	Pri
1843-1850	All modes	1500 W	120 W	2700 Hz	Pri
1850-2000	All modes	15 W	15 W	2700 Hz	Sec
3,5 MHz/80 m 3500-3800 kHz (300 kHz)					
3500-3510	CW, priority for intercontinental operation	1500 W	120 W	200 Hz	Pri
3510-3560	CW, contest preferred	1500 W	120 W	200 Hz	Pri
3555	QRS Centre of Activity				
3560-3570	CW	1500 W	120 W	200 Hz	Pri
3560	QRP Centre of Activity				
3570-3580	Narrow band modes - digimodes	1500 W	120 W	200 Hz	Pri
3580-3590	Narrow band modes - digimodes	1500 W	120 W	500 Hz	Pri
3590-3600	Narrow band modes - digimodes, aut. cont. data stations	1500 W	120 W	500 Hz	Pri
3600-3620	All modes - digimodes, aut. cont. data stations	1500 W	120 W	2700 Hz	Pri
3600-3650	All modes, SSB contest preferred	1500 W	120 W	2700 Hz	Pri
3630	Digital Voice Centre of Activity				
3650-3700	All modes	1500 W	120 W	2700 Hz	Pri
3690	SSB QRP Centre of Activity				
3700-3775	All modes, SSB contest preferred	1500 W	120 W	2700 Hz	Pri
3735	Image Centre of Activity				
3760	Region 1 Emergency Centre of Activity				
3775-3800	All modes, SSB contest preferred, priority for intercontinental op.	1500 W	120 W	2700 Hz	Pri
5 MHz/60 m 5351,5-5366,5 MHz (15 kHz)					
5351,5-5354,0	CW, Narrow band modes	15 W (EIRP)	15 W (EIRP)	200 Hz	Pri
5354,0-5366,0	All modes, USB recommended for voice operation	15 W (EIRP)	15 W (EIRP)	2700 Hz	Pri
5366,0-5366,5	Weak signal narrow band modes	15 W (EIRP)	15 W (EIRP)	20 Hz	Pri
7 MHz/40 m 7000-7200 kHz (200 kHz)					
7000-7040	CW	1500 W	120 W	200 Hz	Pri
7030	QRP Centre of Activity				
7040-7047	Narrow band modes - digimodes	1500 W	120 W	500 Hz	Pri
7047-7050	Narrow band modes - digimodes, aut. cont. data stations	1500 W	120 W	500 Hz	Pri
7050-7053	All modes - digimodes, aut. cont. data stations	1500 W	120 W	2700 Hz	Pri
7053-7060	All modes, Digimodes	1500 W	120 W	2700 Hz	Pri
7060-7100	All modes, SSB contest preferred	1500 W	120 W	2700 Hz	Pri
7070	Digital Voice Centre of Activity				
7090	SSB QRP centre of activity				
7100-7130	All modes	250 W	120 W	2700 Hz	Sec
7110	Region 1 Emergency Centre of Activity				
7130-7175	All modes, SSB contest preferred	250 W	120 W	2700 Hz	Sec
7165	Image centre of activity				
7175-7200	All modes, SSB contest preferred, priority for intercontinental op.	1500 W	120 W	2700 Hz	Pri
10 MHz/30 m 10100-10150 kHz (50 kHz)					
10100-10130	CW	1500 W	120 W	200 Hz	Sec
10116	QRP Centre of Activity				
10130-10150	Narrow band modes, Digimodes	1500 W	120 W	500 Hz	Sec
14 MHz/20 m 14100-14350 kHz (250 kHz)					
14000-14060	CW, contest preferred	1500 W	120 W	200 Hz	Pex
14055	QRS Centre of Activity				
14060-14070	CW	1500 W	120 W	200 Hz	Pex
14060	QRP Centre of Activity				
14070-14089	Narrow band modes - digimodes	1500 W	120 W	500 Hz	Pex
14089-14099	Narrow band modes - digimodes, aut. cont. data stations	1500 W	120 W	500 Hz	Pex
14099-14101	IBP, exclusively for beacons				Pex
14101-14112	All modes - digimodes, aut. cont. data stations	1500 W	120 W	2700 Hz	Pex
14112-14125	All modes	1500 W	120 W	2700 Hz	Pex
14125-14300	All modes, SSB contest preferred	1500 W	120 W	2700 Hz	Pex
14130	Digital Voice Centre of Activity				
14195 ± 5 kHz	Priority for DX-peditions				
14230	Image Centre of Activity				
14285	SSB QRP Centre of Activity				
14300-14350	All modes	1500 W	120 W	2700 Hz	Pex
14300	Global Emergency Centre of Activity				

Taajuus (kHz)	Suositteltu lähetystapa ja käyttötarkoitus	Tehoraja Yleisluokka	Tehoraja Perusluokka	Suurin suositeltu kaistanleveys	Status
18 MHz/17 m 18068-18168 kHz (100 kHz)					
18068-18095	CW	1500 W	120 W	200 Hz	Pex
18086	QRP Centre of Activity				
18095-18105	Narrow band modes - digimodes	1500 W	120 W	500 Hz	Pex
18105-18109	Narrow band modes - digimodes, aut. cont. data stations	1500 W	120 W	500 Hz	Pex
18109-18111	IBP, exclusively for beacons				Pex
18111-18120	All modes - digimodes, aut. cont. data stations	1500 W	120 W	2700 Hz	Pex
18120-18168	All modes	1500 W	120 W	2700 Hz	Pex
18130	SSB QRP Centre of Activity				
18150	Digital Voice Centre of Activity				
18160	Emergency Centre of Activity				
21 MHz/15 m 21000-21450 kHz (450 kHz)					
21000-21070	CW	1500 W	120 W	200 Hz	Pex
21055	QRS Centre of Activity				
21060	QRP Centre of Activity				
21070-21090	Narrow band modes - digimodes	1500 W	120 W	500 Hz	Pex
21090-21110	Narrow band modes - digimodes, aut. cont. data stations	1500 W	120 W	500 Hz	Pex
21110-21120	All modes (not SSB) - digimodes, aut. cont. data stations	1500 W	120 W	2700 Hz	Pex
21120-21149	Narrow band modes	1500 W	120 W	500 Hz	Pex
21149-21151	IBP, exclusively for beacons				Pex
21151-21450	All modes	1500 W	120 W	2700 Hz	Pex
21180	Digital Voice Centre of Activity				
21285	SSB QRP Centre of Activity				
21340	Image Centre of Activity				
21360	Global Emergency Centre of Activity				
24 MHz/12 m 24890-24990 kHz (100 kHz)					
24890-24915	CW	1500 W	120 W	200 Hz	Pex
24906	QRP Centre of Activity				
24915-24925	Narrow band modes - digimodes	1500 W	120 W	500 Hz	Pex
24925-24929	Narrow band modes - digimodes, aut. cont. data stations	1500 W	120 W	500 Hz	Pex
24929-24931	IBP, exclusively for beacons				Pex
24931-24940	All modes - digimodes, aut. cont. data stations	1500 W	120 W	2700 Hz	Pex
24940-24990	All modes	1500 W	120 W	2700 Hz	Pex
24950	SSB QRP Centre of Activity				
24960	Digital Voice Centre of Activity				
28 MHz/10 m 28000-29700 kHz (1700 kHz)					
28000-28070	CW	1500 W	120 W	200 Hz	Pex
28055	QRS Centre of Activity				
28060	QRP Centre of Activity				
28070-28120	Narrow band modes - digimodes	1500 W	120 W	500 Hz	Pex
28120-28150	Narrow band modes - digimodes, aut. cont. data stations	1500 W	120 W	500 Hz	Pex
28150-28190	Narrow band modes	1500 W	120 W	500 Hz	Pex
28190-28199	IBP, regional time shared beacons				Pex
28199-28201	IBP, worldwide time shared beacons				Pex
28201-28225	IBP, continuous duty beacons				Pex
28225-28300	All modes - beacons	1500 W	120 W	2700 Hz	Pex
28300-28320	All modes - digimodes, aut. cont. data stations	1500 W	120 W	2700 Hz	Pex
28320-29000	All modes	1500 W	120 W	2700 Hz	Pex
28330	Digital Voice Centre of Activity				
28360	SSB QRP Centre of Activity				
28680	Image Centre of Activity				
29000-29100	All modes	1500 W	120 W	unrestricted	Pex
29100-29200	All modes - FM simplex - 10 kHz channels	1500 W	120 W	unrestricted	Pex
29200-29300	All modes - digimodes, aut. cont. data stations	1500 W	120 W	unrestricted	Pex
29300-29510	Satellite Links	1500 W	120 W	unrestricted	Pex
29510-29520	Guard Channel				Pex
29520-29590	All modes - FM repeater input (RH1 - RH8)	1500 W	120 W	6000 Hz	Pex
29600	All modes - FM Calling channel	1500 W	120 W	6000 Hz	Pex
29610	All modes - FM Simplex Repeater (parrot, input + output)	1500 W	120 W	6000 Hz	Pex
29620-29700	All modes - FM repeater output (RH1 - RH8)	1500 W	120 W	6000 Hz	Pex

HUOM: Taulukko voi sisältää virheitä, tarkista aina voimassa olevat määräykset ennen kuin lähetät.

Pex = ensisijaiset yksinoikeudet, vain radioamatöörikkennettä, Pri = yhtäläiset ensisijaiset oikeudet, Sec = toissijaiset oikeudet

Taulukko on ladattavissa osoitteesta <https://oh8ta.fi/palvelut/>

Jos huomaat taulukossa virheitä, ilmoita niistä osoitteeseen oh8ta@oh8ta.fi